

# CTDD-6371

## Pixim Seawolf Camera



▲ CTDD-6371

### [ Features ]

- PIXIM 1/3" High Sensitivity Digital Sensor
- High Resolution : 690TVL Effective (Color), 800TVL Effective (B/W)
- Min. Illumination : 0.1Lux (Color), 0.01Lux (B/W)
- Sens-Up (2x~32x)
- Vari-Focal Auto Iris Lens  
- 2.8mm~10mm / F1.2, 3.0mm~9.5mm / F1.0
- Powerful WDR (Wide Dynamic Range)
- True Day & Night for clear image 24 hours
- Private Masking (12 Zones)
- Motion Detection
- OSD for user convenience
- Digital Zoom (4x)
- OSD Control by coaxial cable via pelco coaxitron

### [ Specifications ]

ITEM	CTDD-6371
<b>Power Consumption</b>	12VDC Only (Max.220mA) 24VAC/12VDC (Max240mA/360mA)
<b>Image Sensor</b>	PIXIM 1/3" High Sensitivity Digital Sensor
<b>Effective Pixels</b>	758(H) x 540(V)
<b>Dynamic Range</b>	120dB(Max), 102dB(Typical)
<b>Horizontal Resolution</b>	690TVL Effective (Color), 800TVL Effective (B/W)
<b>Min. Illumination</b>	0.1Lux (Color) 0.01Lux (B/W)
<b>Day &amp; Night</b>	Auto / Color / B/W
<b>White Balance</b>	Auto / AWB / Indoor / Outdoor / Manual
<b>WB Range</b>	2000°K~11,000°K
<b>Shutter Speed</b>	up to 1/30, 720 sec
<b>Sens-up</b>	Auto / Off (Selectable x2 ~ x32)
<b>Privacy Masking</b>	12 Zones
<b>Remote Control</b>	RS-485
<b>AGC</b>	Low / Auto / High / Off
<b>Image Flip</b>	Horizontal and Vertical
<b>Camera ID</b>	On / Off
<b>S/N Ratio</b>	More than 50dB
<b>Video Output</b>	Composite video output 75 ohm terminated
<b>OSD</b>	Built-in
<b>Sync. System</b>	Internal / Line Lock
<b>Operating Humidity</b>	30% ~ 90% RH
<b>Operating Temp.</b>	10°C to 50°